



VOLVO - DEUTZ - Ø 108

87-71494-STD



Motor Özellikleri
(Engine Specifications)

İmalatçı (Manufacturer):
VOLVO - DEUTZ
Çap (Diameter): Ø 108
FM Grup No: 450111

TCD 2013 Euro3
LO62V

6 Sil. Dizel 7146cc 184
kW (250 HP) C. Rail R7


TCD 2013 Euro3
LO42V

4 Sil. Dizel 4764cc
120-129 kW /163-175
PS 18, 1:1

Piston Ölçüleri
(Piston Dimensions)

A : 71.150
B- : 19.600
BØ : 64.000
BX : 4.000
BY : 2.000
D : 108.000
E : 14.040

Pim : 42 x 86


Piston Özellikleri
(Piston Features)

Segman Taşıyıcı
(Ring Carrier)
Yağ Püskürtme Oyuğu
(Oil Jet Cut-Out)
Gözarası Konik
(Conical Eye Gap)

Piston Parça No
(Piston Part No)



87-136900-62
87-71494-STD


Segman Seti
(Ring Set)

06-136900-00-STD

3.000 CK KV1
2.000 NTP KV1
3.500 CRP STD
Goetze® LKZ-Ring®


Silindir Gömleği
(Liner)

14-480040-00-WH
B : 118.000
L : 229.100
D : 128.500
C : 9.000
F : 1.100

O RİNG BİLGİ
(O Ring Information)
24-35047-30/O
2 X (112*3) FKM
PEROXIDE

Silindir Kit
(Assembly Set)

89-136900-62-STD
89-71494-STD

Piston - Blok Montaj
Yüksekliği
(Piston - Block
Assembly Height)

1.15 mm Conta ile
(With Gasket)
0,31/0,40

1,25 mm Conta ile
(With Gasket)
0,41 / 0,50

14-480720-00-WH
B : 120.000
L : 229.100
D : 128.500
C : 9.000
F : 1.100

DIŞ YÜZEYİ FOSFAT
KAPLI
(Outer Surface
Phosphate Coated)

89-136900-72-STD
89-71494-STD




VOLVO-KHD - Ø 108


87-71494-STD



Motor Özellikleri
(Engine Specifications)



Piston Ölçüleri
(Piston Dimensions)




Piston Parça No
(Piston Part No)




Segman Seti
(Ring Set)



Silindir Gömleği
(Liner)



Silindir Kit
(Assembly Set)



Piston - Blok Montaj
Yüksekliği
(Piston - Block
Assembly Height)

14-480040-00-WH
O RİNG BİLGİ
(O Ring Information)
24-35047-30/O
2 X (112*3) FKM
PEROXIDE

14-480041-00-WH
B : 118.000
L : 229.100
D : 128.500
C : 9.500
F : 1.100

Flanş Kalınlığı ve
Flanş alt boğaz çapı
+0,50 mm farklı
(Flange Thickness and
Flange lower throat
diameter+0.50mm
different)

14-480042-00-WH
B : 118.000
L : 229.100
D : 128.500
C : 10.000
F : 1.100

Flanş Kalınlığı ve
Flanş alt boğaz çapı
+1,00 farklı çalışması
(Flange Thickness and
Flange lower throat
diameter+1.00mm
different)

